

| SPARKLING WHITE



DESCRIPTION

Sparkling White is pure white of superior quality, exclusively quarried at VD Marble quarry. Processed using state of the art Italian technology, its unique mineral composition comes alive and glistens the best under spotlight.

AVAILABLE FINISHES

- Polished
- Leather

APPLICATION

- Interior cladding
- Exterior cladding
- Interior flooring



POLISHED



LEATHER

PHYSICAL TEST RESULTS

PROPERTIES	INDICATORS	NORM
Density	2710 kg/m ³	ASTM C97/ C97M-15 (*) EN 1936
Open porosity	0,4%/0,5%/0,6% (*)	ISO:10545-3:1995
Water absorption	0.8%	ASTM C97/ C97M-15 EN 13755
Compressive strength	58.4 MPa (dry cond.) 57	ASTM C880/ C880M-15
Flexural strength	12.6 Mpa -dry cond., 12-wet cond.	ASTM C99/ C99M-15 (*)
Resistance to abrasion	12.5 HS, 19.5 mm ³	ASTM, EN
Frost resistance	No structural change under -18C	ASTM A 326-3
Slip resistance	R9 (**), R10 (***)	DIN51130, EN 14231
Fire resistance	Resistant	ISO 1182:2010

(*) - Polished/Leathered/Bush Hammer & Sandblasted

(**) - Polished, Leather (interior living areas, offices, retail, hallway, corridors)

(***) - Sandblasted & Bush Hammer (interior, exterior)



Quarry, Processing & Marble Export
SLAB | TILES